

L-1A

Direct-drive, 1-needle, Lockstitch Machine with Automatic Thread Trimmer
(Nipper and Automatic reverse feed device)

Enhancement of basic functions



Operation panel and control box are integrated with the machine head

The sewing machine has been integrated with the operation panel and the control box for ease of use. All of the L-1A series adopt the direct drive system. As a result, the sewing machine starts up swiftly and promises increased stop accuracy, responsiveness. thereby demonstrating improved thereby demonstrating improved.




Operation panel



Control box

● Nipper device

This device pulls the needle thread into the wrong side of the material at the beginning of sewing, thereby ensuring more beautifully-finished seams.



Nipper device



USB port

● Direct-drive type

Since the sewing machine has no V-belt, the operator needs neither to clean up shavings from the V-belt, nor adjust the V-belt tension.

● USB port

The L-1A series is equipped as standard with a USB port that can be used to charge smartphones, etc.

LED light

The LED light is located on the underside of the arm jaw. It reduces operator fatigue and improves work efficiency. It is provided as standard for all models of the L-1A Series. In addition, the illuminance of the LED lights can be adjusted in three steps and can be used as an auxiliary light for work.



LED light

Rotary thread-trimming mechanism

The machine adopts a single-blade drive rotary thread-trimming mechanism, so it is easy to maintain.

SPECIFICATIONS

Model name	L-1A-M	L-1A-H
Application	Medium-weight	Heavy-weight
Max. sewing speed	5,000sti/min*	3,500sti/min*
Max. stitch length	5mm	
Lift of the presser foot	By hand: 5.0mm / By knee: 13mm	
Needle	DBx1 (#14) #11-#18	DPx5 (#21) #16-#21
Nipper	provided	
Lubrication	Automatic	
Lubricating oil	JUKI MACHINE OIL 7 (equivalent to ISO VG7)	
Power consumption	488 VA	
Power requirement	Single-phase 220V/Single-phase 110V	

* sti/min is the abbreviation for "stitches per minute"

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows:

Machine head & Control box

Voltage	Code	Auto-lifter	Code
Single-phase 200~240V	A	Provided	AK
Single-phase 110V	L	Not Provided	—

L 1 A - [] [] [] [] - []

Application	Code	Destination	Code
for Medium weight materials	M	General export	A
for Heavy weight materials	H	India	F
		Turkey (for RoHS)	H

JUKI JUKI CORPORATION
SEWING MACHINERY & SYSTEMS BUSINESS UNIT

2-11-1, TSURUMAKI, TAMA-SHI, TOKYO 206-8551, JAPAN
PHONE: (81) 42-357-2370 FAX: (81) 42-357-2274
<https://www.juki.co.jp/en>

- Specifications and appearance are subject to change without prior notice for improvement.
- Read the instruction manual before putting the machine into service to ensure safety.